

# 4FWXN

**1**

**2**

**IN BASSO**  
**BOTTOM SIDE**

Spess.vetro Glass thk.	Guarnizioni per ogni lato Gaskets each side
8 [5/16"]	4x 1mm [4x 3/64"]
10 [25/64"]	3x 1mm [3x 3/64"]
12 [15/32"]	2x 1mm [2x 3/64"]
12,72 [1/2"]	2x 0,8mm [2x 1/32"]
13,52 [17/32"]	1x 0,8mm + 1x 0,5mm [1x 1/32" + 1x 1/64"]
14 [9/16"]	1x 1mm [1x 3/64"]

**3**

12 Nm  
[8.85 lbf ft]

**4**

Spess.vetro Glass thk.	Guarnizioni per ogni lato Gaskets each side
8 [5/16"]	2x 1+1,8mm [2x 3/64"+5/64"]
10 [25/64"]	2x 1,8mm [3x 5/64"]
12 [15/32"]	2x 1mm [2x 3/64"]
12,72 [1/2"]	2x 0,8mm [2x 1/32"]
13,52 [17/32"]	2x 0,6mm [2x 1/64"]

**IN ALTO**  
**UPPER SIDE**

**5**

16 Nm  
[11.8 lbf ft]

**6**

AS PER REQUEST  
100mm  
[3" 15/16] min

**7**

AS PER REQUEST  
(100mm [3" 15/16] min)

27  
37 1" 1/16  
1" 29/64

**8**

Ø8  
5/16"

**9**

**10**

**11**

**NO**

**12**

**13**

**14**

**15**

**16**

±4  
±5/32"

**17**

±4  
±5/32"

**18**

**19**

14 Nm  
[10.3 lbf ft]

**20**

Speed Adjustment

**21**

**22**

**23**

**24**